



PRINT



SAVE AS PDF

# MAG 1<sup>®</sup> NON-DETERGENT 30 LUBRICATING OIL

NON-DETERGENT LUBRICATING OIL INDUSTRIAL LUBRICANTS AND GEAR OILS



Featuring MAG 1<sup>®</sup> with FMX<sup>®</sup> Technology – Friction Management for Xtreme protection™. MAG 1<sup>®</sup> provides unsurpassed protection and performance.

MAG 1<sup>®</sup> Non-Detergent Lubricating Oils are recommended for compressors and hydraulic systems which require non-detergent oils. Non-detergent oils are effective in the lubrication of bearings and chains in non-critical once-through systems. Not for use in automotive gasoline engines.

## POWERFUL ANTI-FRICTION, ANTI-WEAR CHEMISTRY

MAG 1<sup>®</sup> provides outstanding control of friction and wear. Advanced molecules bond together to create a wear-resistant shield that works to build barriers that reduce friction and wear.

## EVOLUTIONARY PERFORMANCE™

OEMs continue to evolve equipment designs and operating conditions are becoming more severe. One brand has evolved right alongside today's equipment – MAG 1<sup>®</sup>. Only the most advanced driveline gear oils meet the difficult challenges of effectively balancing performance, strength and durability.

## TYPICAL PROPERTIES

Color	ASTM D1500	3.0
Flash Point °C	ASTM D92	230
Flash Point °F	ASTM D92	446
Gravity, °API	ASTM D287	30.58
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.873
Viscosity @ 100°C cSt	ASTM D445	10.13
Viscosity @ 40°C cSt	ASTM D445	79.17
Viscosity Index	ASTM D2270	109

## CONTAINER/BULK AVAILABILITY

6/1 Quart	Product Number - 68761
55 Gallon Drum	Product Number - 62859
2/2.5 Gallon	Product Number - 00232

## Available in Bulk

Information accurate as of March 3, 2024