



PRINT



SAVE AS PDF

MAG 1[®] SAE 10 HEAVY DUTY DIESEL ENGINE OIL

MONOGRADE HEAVY DUTY DIESEL ENGINE OIL HEAVY DUTY ENGINE OIL

Featuring MAG 1[®] with FMX[®] Technology – Friction Management for Xtreme protection[™]. Provides unsurpassed protection for new and old engine designs.



PERFORMANCE

- FMX Technology provides unsurpassed protection.

STRENGTH

- FMX Technology provides a very strong oil film to prevent metal-to-metal contact.

DURABILITY

- FMX Technology stands up to high heat and shearing to protect as well on the last day as it does on the first day.

APPLICATIONS

- For older diesel engines.

INDUSTRY/OEM SPECIFICATIONS

API CF	Meets Requirements
--------	--------------------

TYPICAL PROPERTIES

Cold Cranking Simulator at (°C), cP	ASTM D5293	4025 (-25)
Color	ASTM D1500	2.5
Flash Point °C	ASTM D92	206
Flash Point °F	ASTM D92	403
Gravity, °API	ASTM D287	31.42
Pour Point °C (°F)	ASTM D5950	-36°C (-33°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8685
Viscosity @ 100°C cSt	ASTM D445	6.794
Viscosity @ 40°C cSt	ASTM D445	42.83
Viscosity Index	ASTM D2270	114
Zinc, wt. %	ASTM D5185	0.086

CONTAINER/BULK AVAILABILITY

6/1 Quart	Product Number - 64097
55 Gallon Drum	Product Number - 62852

Available in Bulk

Information accurate as of March 3, 2024