



# MAG 1<sup>®</sup> SAE 30 HEAVY DUTY DIESEL ENGINE OIL

### MONOGRADE HEAVY DUTY DIESEL ENGINE OIL HEAVY DUTY ENGINE OIL





#### PERFORMANCE

• FMX Technology provides unsurpassed protection.

#### **STRENGTH**

• FMX Technology provides a very strong oil film to prevent metal-to-metal contact.

#### **DURABILITY**

• FMX Technology stands up to high heat and shearing to protect as well on the last day as it does on the first day.

#### **APPLICATIONS**

• For older diesel engines.

#### INDUSTRY/OEM SPECIFICATIONS

API SN Plus	Approved
API CF	Meets Requirements
API CF-2	Meets Requirements

#### TYPICAL PROPERTIES

Color	ASTM D1500	2.5	
Flash Point °C	ASTM D92	208	
Flash Point °F	ASTM D92	406	
Gravity, °API	ASTM D287	30.03	
Pour Point °C (°F)	ASTM D5950	-30°C (-22°F)	
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.876	
Viscosity @ 100°C cSt	ASTM D445	10.91	
Viscosity @ 40°C cSt	ASTM D445	91.05	
Viscosity Index	ASTM D2270	105	
Zinc, wt. %	ASTM D5185	0.086	

2/2.5 Gallon	Product Number - 00312
330 Gallon Tote	Product Number - 62086
55 Gallon Drum	Product Number - 62854
5 Gallon Pail	Product Number - 00034
2/2.5 Gallon	Product Number - 00132
6/1 Quart	Product Number - 61656

## Available in Bulk

Information accurate as of September 9, 2021