



PRINT



SAVE AS PDF

MAG 1[®] SAE 30 HEAVY DUTY DIESEL ENGINE OIL

MONOGRADE HEAVY DUTY DIESEL ENGINE OIL HEAVY DUTY ENGINE OIL

Featuring MAG 1[®] with FMX[®] Technology – Friction Management for Xtreme protection[™]. Provides unsurpassed protection for new and old engine designs.



PERFORMANCE

- FMX Technology provides unsurpassed protection.

STRENGTH

- FMX Technology provides a very strong oil film to prevent metal-to-metal contact.

DURABILITY

- FMX Technology stands up to high heat and shearing to protect as well on the last day as it does on the first day.

APPLICATIONS

- For older diesel engines.

INDUSTRY/OEM SPECIFICATIONS

API CF	Meets Requirements
API CF-2	Meets Requirements

TYPICAL PROPERTIES

Color	ASTM D1500	2.5
Flash Point °C	ASTM D92	208
Flash Point °F	ASTM D92	406
Gravity, °API	ASTM D287	30.03
Pour Point °C (°F)	ASTM D5950	-30°C (-22°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.876
Viscosity @ 100°C cSt	ASTM D445	10.91
Viscosity @ 40°C cSt	ASTM D445	91.05
Viscosity Index	ASTM D2270	105
Zinc, wt. %	ASTM D5185	0.086

CONTAINER/BULK AVAILABILITY

6/1 Quart	Product Number - 61656
2/2.5 Gallon	Product Number - 00132
5 Gallon Pail	Product Number - 00034
55 Gallon Drum	Product Number - 62854
330 Gallon Tote	Product Number - 62086

Available in Bulk

Information accurate as of July 7, 2025